

# MSDS Material Safety Data Sheet

**AIOD**



## SERVICE PRO NON-CHLORINATED BRAKE CLEANER-SP4605

MSDS Number: SP4605

Revision Date: 08/08/2007

Page 1 of 4

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer

AIOD  
ASSOCIATION OF INDEPENDENT OIL DISTRIBUTORS  
700 S. CASCADE  
MONTROSE, CO 81401

#### Contact:

Telephone Number: (970) 249-6336

FAX Number: (970) 240-4131

E-Mail:

Web

**Product Name:** SERVICE PRO NON-CHLORINATED BRAKE CLEANER-SP4605  
**Revision Date:** 08/08/2007  
**MSDS Number:** SP4605  
**Common Name:** BRAKE CLEANER CONTAINING ORGANIC SOLVENTS

EMERGENCY PHONE NUMBER (800) 752-7869

NFPA 704M RATING :

HEALTH:2 FIRE:4 REACTIVITY:0 SPECIAL:

O=INSIGNIFICANT 1=SLIGHT 2=MODERATE 3=HIGH 4=EXTREME

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

ACETONE	67-64-1	52%-56%
HEPTANE	142-82-5	31%-35%
XYLENE	1330-20-7	7%-11%
ETHYLBENZENE	100-41-4	1%-5%

### 3 HAZARDS IDENTIFICATION

**Route of Entry:** Skin absorption and inhalation  
**Target Organs:** Lungs, kidneys, liver and nervous system.  
**Inhalation:** Respiratory irritation and dizziness  
**Skin Contact:** Prolonged contact with skin can cause irritation. Repeated skin contact may cause persistent irritation and dermatitis  
**Eye Contact:** Will cause irritation upon contact.  
**Ingestion:** Product may cause discomfort, nausea, vomiting and diarrhea.

**CARCINOGENICITY:** Product is not considered a carcinogen by OSHA, NTP or IARC.

**MEDICAL CONDITIONS:** Pre-existing eye or skin conditions may be aggravated by over-exposure to this product.

# MSDS Material Safety Data Sheet

**AIOD**



## SERVICE PRO NON-CHLORINATED BRAKE CLEANER-SP4605

MSDS Number: SP4605

Revision Date: 08/08/2007

Page 2 of 4

### 4 FIRST AID MEASURES

- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. Seek medical attention. Inhalation hazard unlikely due to low volatility of product.
- Skin Contact:** Wash area with soap and water. seek medical attention if irritation persists
- Eye Contact:** Immediately flush eyes with plenty of water for 15 minutes. Seek medical attention.
- Ingestion:** DO NOT induce vomiting. Only give CONSCIOUS victim two glasses of water and seek medical attention. NEVER give UNCONSCIOUS anything by mouth.

### 5 FIRE FIGHTING MEASURES

- Flash Point:** 2 degrees F  
**Flash Point Method:** TCC

**EXTINGUISHING MEDIA:** Carbon Dioxide ( CO2) Dry Chemical, Foam.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors are heavier than air and can collect in low areas

**FIRE FIGHTING INSTRUCTIONS:** Containers can build up pressure if exposed to fire. Containers should be cooled with water supply.

**FIRE FIGHTING EQUIPMENT:** Self- contained breathing apparatus with full face piece operated in positive pressure mode.

### 6 ACCIDENTAL RELEASE MEASURES

**SPILL/LEAK PROCEDURES:** Notify safety personnel ,evacuate all unnecessary personnel and provide adequate ventilation. If feasible, and without risk, clean-up personnel should stop leak. All clean up personnel should wear proper personal protective equipment.

**SMALL SPILLS:** Clean with inert absorbent and place in recovery drums for disposal.

**LARGE SPILLS:** Dike to prevent further migration of material. DO NOT release into waterways or sewers. Follow applicable federal and state regulations.

### 7 HANDLING AND STORAGE

- Handling Precautions:** Wash thoroughly after handling. Do not get into eyes, on skin or on clothing.. Do not smoke while using this product. Do not use near excessive heat, sparks, or open flame.
- Storage Requirements:** Store in clean, dry locations away from excessive heat. Store in areas designated for the storage of flammable liquids according to NFPA 30 ( Flammable and Combustible Liquids Code)

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering Controls:** Eye wash station and safety shower.  
Strong general ventilation or local exhaust.
- Protective Equipment:** EYE: Chemical splash goggles with indirect or no ventilation.  
SKIN :Chemical resistant gloves such as nitrile.  
RESPIRATORY: Organic vapor air purifying respirator if vapors are a nuisance or if the concentrations are above PEL or TLV.  
Never eat drink or smoke in the work area.

# MSDS Material Safety Data Sheet

**AIOD**



## SERVICE PRO NON-CHLORINATED BRAKE CLEANER-SP4605

MSDS Number: SP4605

Revision Date: 08/08/2007

Page 3 of 4

### 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Colorless liquid	<b>Boiling Point:</b>	133 - 289 F
<b>Physical State:</b>	liquid	<b>Freezing/Melting Pt.:</b>	
<b>Odor:</b>	petroleum distillate	<b>Solubility:</b>	Not soluble in water
<b>pH:</b>		<b>Spec Grav./Density:</b>	0.7641
<b>Vapor Pressure:</b>	44.0 - 125.0 mmHG		
<b>Vapor Density:</b>	>1.0		
<b>VOC:</b>	<45 %		
<b>Evap. Rate:</b>	>1.0		

### 10 STABILITY AND REACTIVITY

<b>Stability:</b>	Material is stable.
<b>Conditions to avoid:</b>	Excessive heat and open flame.
<b>Materials to avoid (incompatibility):</b>	Strong oxidizing agents.
<b>Hazardous Decomposition products:</b>	Carbon Monoxide and Carbon Dioxide
<b>Hazardous Polymerization:</b>	Cannot occur.

### 11 TOXICOLOGICAL INFORMATION

LD50

Acetone:	10.7 ml/kg (oral)
Xylene:	7.53 g/kg (oral)
n-Heptane:	No data

### 12 ECOLOGICAL INFORMATION

No data.

### 13 DISPOSAL CONSIDERATIONS

As a waste, this product in its raw form DOES MEET the criteria of a hazardous waste as defined by RCRA (40CFR361). Dispose of in accordance with all applicable state, federal and local regulations.

### 14 TRANSPORT INFORMATION

DOMESTIC: Flammable Liquids, n.o.s., (Acetone), Class 3, UN1993, PGII.

EXPORT: \*Flammable Liquids, n.o.s., (Acetone), Class 3, UN1993, PGII, FP -16 Ccc.

# MSDS Material Safety Data Sheet

**AIOD**



## SERVICE PRO NON-CHLORINATED BRAKE CLEANER-SP4605

MSDS Number: SP4605

Revision Date: 08/08/2007

Page 4 of 4

### 15 REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS

OSHA: Considered to be a hazardous material as defined by 29CFR1910.1200

#### EPA SARA TITLE III

Section 311-312 (40CFR370): If stored in excess of the threshold quantities, this product should be reported as a(n):

IMMEDIATE (acute) HEALTH HAZARD  
DELAYED (chronic) HEALTH HAZARD  
FIRE HAZARD

Section 313(40CFR372) This product contains ingredients which are subject to the reporting requirements of SARA 313:

Xylene 9%  
Ethylbenzene <3%

### 16 OTHER INFORMATION

CALIFORNIA PROPOSITION 65: This product does contain ingredients which are on the current Proposition 65 list.

Ethylbenzene

END OF MSDS DOCUMENT