

SERVICE PRO® AUTOMATIC TRANSMISSION FLUID MULTI-PURPOSE ATF Manufactured with virgin base oils

DESCRIPTION: SERVICE PRO® Automatic Transmission Fluid Multi-Purpose ATF is a multi-purpose automatic transmission fluid (ATF) and is recommended as a replacement fluid for automatic transmissions meeting original equipment manufacturer's (OEM) performance requirements of General Motors, Ford, and other domestic and imported passenger cars, vans and light trucks where Dexron II, Dexron II-E, Dexron III-G, Dexron III, H Revision, Automatic Transmission Fluid, or Ford Mercon fluids are specified. It is also, recommended for Allison TES 389, C-3, C-4 applications, and Caterpillar TO-2 applications. SERVICE PRO® Automatic Transmission Fluid Multi-Purpose ATF is suitable for most power steering units. Other manufacturer suggested applications include mobile hydraulic and industrial systems, and rotary air compressors under certain service conditions.

Not for use in vehicles requiring Ford Type F, Mercon V, SP, LV, Chrysler ATF fluids, or Dexron VI. Not for use in 6-speed or continuously variable transmissions (CVT). Always check your owner's manual for proper application

PERFORMANCE BENEFITS:

- Excellent low temperature fluidity for good cold-start shifting
- Resistance to foaming
- Oxidation and thermal stability for long life
- Protection against rust, corrosion and wear
- Multiple approvals for lower inventory requirements
- Compatible with all transmission seal material

TYPICAL PROPERTIES:

Appearance	Red, Dyed
Viscosity	
@ 40 °C, cSt	33.37
@ 100 °C, cSt	6.87
Viscosity Index	161
Pour Point, °F	-50
API Gravity	33
Specific Gravity @ 60°F	0.8602
Pounds per gallon	7.163
Flash Point COC, °F	405
Dexron III G	Y
Dexron III H	Y
Mercon	Y
Allison C-4	Y
Cat TO-2	Y

