

## SERVICE PRO® PREMIUM MULTI VEHICLE SYNTHETIC BLEND ATF

Manufactured with virgin base oils

**DESCRIPTION:** SERVICE PRO® Premium Multi Vehicle Synthetic Blend ATF is a new generation automatic transmission fluid recommended for use in automobile and truck transmissions, power-shift transmissions and other types of service requiring an approved Ford Mercon® V, Mercon®, Dexron® III-H or Allison C-4 automatic transmission fluid. It is approved for use in Voith Transmissions. Approved for ZF applications TE-ML 03D, 04D, 14B, 16L and 17C.

SERVICE PRO® Premium Multi Vehicle Synthetic Blend ATF is also recommended for service fill in Mercon, Chrysler, Honda/Acura, Hyundai, Jeep, Mercedes-Benz, Mitsubishi (Diamond SP-II or SP-III), Nissan (Matic D, J or K)/Infiniti, Saturn, Toyota (T-III & T-IV)/Lexus/Scion, VW/Audi, most European vehicles including BMW & Volvo, most Asian vehicles including Daewoo, Isuzu, Kia, Mazda, and Suzuki.

SERVICE PRO® Premium Multi Vehicle Synthetic Blend ATF is not for use in transmissions requiring Ford Type F or Dexron® VI, Mercon® SP, LV or in Continuously Variable Transmission (CVT) applications. Always consult your owner's manual where specific automatic transmission fluids are recommended.

- PERFORMANCE BENEFITS:**
- Outstanding resistance to oxidative and thermal breakdown
  - Exceptional low temperature fluidity
  - Excellent anti-wear properties.
  - Stable friction properties
  - Excellent gear shift quality throughout service life.

**TYPICAL PROPERTIES:**

Gravity, API	32.4
Density, lbs/gals	7.17
Flash, COC, °F	352
Viscosity	
@ 40 Deg. C, cSt	32.6
@ 100 Deg. C, cSt	7.32
Viscosity Index	200
Brookfield Viscosity cP @ -40°C	
Max	12,000
Color	Red
Voith	Service bulletin #013 & 118
ZF	TE-ML 03D, 04D, 14B 16L, 17C



## SERVICE PRO® PREMIUM MULTI VEHICLE SYNTHETIC BLEND ATF

**Service Pro Multi-Vehicle Synthetic Blend ATF is suitable for use  
in the following applications:**

Allison C-4	Mercedes-Benz 236.3
Audi G-052-025-A1	Mercedes-Benz 236.5
Audi G-052-025-A2	Mercedes-Benz 236.7
Audi G-052-162 A1/A2	Mercedes-Benz 236.9
BMW LA2634	Mercedes-Benz 236.10
BMW LT71141	Mitsubishi Diamond SP-II
Chrysler ATF +4® *	Mitsubishi Diamond SP-III
Dexron® *	Nissan Matic-D
Dexron® -II*	Nissan Matic-J
Dexron® -III D*	Nissan Matic-K
Dexron® -III G*	Shell LA2634
Dexron® -III H*	Subaru ATF HP
Esso LT 71141	Texaco 7045-E
Ford Mercon® *	Texaco ETL-8072 B
Ford Mercon® V*	Texaco N402
Honda/Acura ATF-Z1 (except CVT's)	Toyota Type T-III
Hyundai SP-II	Toyota Type T-IV
Hyundai SP-III	Voith 55.6335.32 (G607), IM1107552A
Idemitsu K17	Volvo 97340
JWS 3309	VW G 052 990 A2 (09A)
Kia SP-II	VW G 055 025 A2 (09G)
Kia SP-III	ZF TE-ML 03D
Kia RED-1K	ZF TE-ML 04D
MAN 339 V1	ZF TE-ML 14A
MAN 339 Z1	ZF TE-ML 14B
MAN 339 Z2	ZF TE-ML 16L
Mazda ATF-111	ZF TE-ML 17C
Mazda ATF-MV	

\*Chrysler ATF +4® is a registered trademark of Chrysler Group LLC./ Dexron® is a registered trademark of General Motors Corp./ Mercon® is a registered trademark of Ford Motor Company