

# SERVICE PRO® PREMIUM DEXRON® VI AUTOMATIC TRANSMISSION FLUID

Manufactured with virgin base oils

**DESCRIPTION:** SERVICE PRO® Premium DEXRON® VI Automatic Transmission Fluid is the latest generation automatic transmission fluid approved by General Motors for use in vehicles with automatic transmissions. This unique full synthetic fluid is specially formulated to provide twice the service life of a DEXRON®-III (H) ATF and offers improved performance for new and older transmissions. It is formulated to provide improved oxidation stability, shear stability, friction durability, and wear protection to help meet warranty protection requirements in late model vehicles.

**APPLICATIONS:** SERVICE PRO® Premium DEXRON® VI Automatic Transmission Fluid is recommended for all 2006 and later GM vehicles with Hydramatic automatic transmissions. It is fully back serviceable for DEXRON®-III (H), (G), III and IIE applications. Meets GM specification GMN10060.

**PERFORMANCE BENEFITS:** When compared to DEXRON®-III (H) ATF, SERVICE PRO® Premium DEXRON® VI Automatic Transmission Fluid provides the following benefits:

- Extends the life of the transmission
- Improved oxidation and thermal stability
- Enhanced foam control
- Full synthetic formula
- Outstanding low temperature performance
- Superior antiwear protection
- Improved torque transfer

**TYPICAL PROPERTIES:**

SAE Grade		
Appearance	Viscosity	Red, dyed
@ 40 Deg. C,	cSt	29.8
@ 100 Deg. C,	cSt	6
@ 100 Deg. F,	SUS	152
@ 210 Deg. F,	SUS	46.3
@ -40° C,	max	12,000
@ -30° C,	max	3,150
@ -20° C,	max.	1,050
Viscosity Index		151
API Gravity		35.6
Sp. Gr. @ 60°F		0.8468
Flash, COC, °F		405
Pour Pt. °F		-65
Service Pro Part #		17095