

SERVICE PRO® PREMIUM TRACTOR TRANSMISSION & HYDRAULIC FLUID

DESCRIPTION: SERVICE PRO® Premium Tractor Transmission & Hydraulic Fluid is a high quality, specially designed lubricant containing anti-rust, anti-foam and oxidation inhibitors; plus other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is an “all-seasonal” type of oil that resists thickening in cold weather and thinning in the heat of the summer. It is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition; and provides excellent protection against seal and pump deterioration. Operators, especially farmers, will appreciate the multipurpose application of SERVICE PRO® Premium Tractor Transmission & Hydraulic Fluid for transmissions, final drives, and hydraulic systems of tractors thereby eliminating the requirement to inventory a variety of oil products.

SERVICE PRO® Premium Tractor Transmission & Hydraulic Fluid is currently being used in a variety of mechanical systems world-wide.

**PERFORMANCE
BENEFITS:**

- Excellent gear, bearing and pump wear protection
- Multi-functional fluid
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection
- Reduces brake chatter
- Compatibility with oil seal materials used in transmission and hydraulic systems

TYPICAL PROPERTIES:	SAE Grade	10W20
	SAE Grade, Gear	75
	Viscosity	
	@ 40 Deg. C, cSt	55
	@ 100 Deg. C, cSt	9.2
	@ 100 Deg. F, SUS	260
	@ 210 Deg. F, SUS	58
	Viscosity Index	140 (min)
	Flash Point, Deg. F	400
	Pour Point, Deg. F	-40
Gravity, Deg API @ 60F	28.2	
Density, lb/gal	7.38	
Service Pro Part #	16696	





SERVICE PRO® PREMIUM TRACTOR TRANSMISSION & HYDRAULIC FLUID

APPLICATION: SERVICE PRO® Premium Tractor Transmission & Hydraulic Fluid is recommended for use in equipment made by:

Allison – Hydraulic Trans Fluid; GMC, Type C, C-1, C-2, C-3, C-4
Allis-Chalmers - #272843, Part # 924282 (Power Fluid No. 821), Part # 246634
Caterpillar – Anti-wear Hydraulic Oil above -10 Deg. F; TO-2
Clark Transmissions
Deutz-Allis – 272843 (Power Fluid 821XL)
J.I. Case – Hi-Lo CH Fluid JIC 145, Case-O-Matic Type A, JIC 143, JIC 144, JIC-C-185 (TFD), MS-1205 (TFD-II), MS-1206 (PTF), MS-1207 (Hy-Trans-Plus), MS-1201, MS-1209
Ford New Holland – M-2C41 Selecto-Speed Fluid, ESN M-2-C41A, M-2C41-B, M-4864A, M-2C65A, M-2C77A, M-4864B, M-2C65B, M-2C78A, M-2C86A, M-2C134B. M-2C 134D, FNHA-2-C-200 & 201
Hesston Fiat AF-87
International Harvester – Hy-Trans Fluid, (B-5, B-6, B-7)
John Deere – Fluid Type 303 (J-14C), Part #AR-284254, Part #AR-269444, J-14B, J-20A, J-20B (Hy-Guard), J-20C, Quatrol Requirements, J21A
Kubota UDT Fluid, Super UDT Fluid
Landini
Massey Ferguson – M-1103A, M-1103B. M-1110, M-129A, M-1135, Permatran III, M-1141
Oliver – Where Additive Part # 102082A is mixed with 10W, 5W20, 10W30 oil; in 1 part to 16 parts oil, Type 55 and Renk 874 A/B Transmission
White Universal Fluid
Stieger – Hydraulic Trans Fluid. Gear, Hydraulic and Wet Brake Oil
Sunstrand Pumps
Versatile – Specs. 23M or 24M
White Farm – Hydraulic Oil Type 55 Fluid, White Universal Fluid, White Farm Q-1760, Q-1766B, White UTHF, Q-1826.