

SERVICE PRO™

Premium Lubricants

SERVICE PRO® PREMIUM HD SINGLE-VISCOSITY GRADE ENGINE OILS

DESCRIPTION: Service Pro® Premium Single-Viscosity Grade Engine Oils are high quality, heavy-duty crankcase oils. This product line is manufactured with the latest additive technologies to provide excellent performance. SAE 30 and 40 viscosity grades are designed with low sulfated ash to give optimal performance in Detroit Diesel Two Stroke Cycle diesel engines calling for API CF-2. These mono-grade products also meet the performance requirements of API CF. SAE 10W and SAE 30 viscosity grades have also passed the requirements of the Allison C-4 specification. These lower viscosity grade fluids are excellent for hydraulic applications calling for Allison C-4 and / or Caterpillar TO-2 performance with engine oil type technology additive systems.

PERFORMANCE BENEFITS:

- Excellent detergency control of exhaust port deposits in Detroit Diesel Two-stroke cycle diesel engines.
- Excellent dispersancy and oxidation resistance protect against excessive viscosity increase.
- Superior wear protection in hydraulic pumps and Detroit Diesel Two-stroke cycle diesel engines.
- Good TBN properties protect against corrosive wear.
- Proven oil consumption control in heavy duty service.
- Shear stability of mono-grades assures stay-in-grade performance.
- Meets Detroit Diesel recommendations of 1.0% maximum sulfated ash for Two-stroke cycle diesel engines.

Caterpillar TO-2
Detroit Diesel Two-stroke Cycle diesel engines

Allison C-4
US CID A-A-52306

*Some performance capabilities are applicable to specific viscosity grade(s).

Service Pro® Premium Single-Viscosity Grade Engine Oils are intended for use in heavy-duty service in commercial trucks, agricultural equipment, construction equipment, and other diesel fueled engine, hydraulic, and transmission applications. Specific viscosity grades are approved for use in power-shift, manual, and hydrostatic transmissions, final drives, and hydraulic systems where the equipment manufacturer designates the use of a heavy-duty, detergent-type engine oil. Check Owners' Manuals for specific viscosity grade and API Service Category recommendations.

TYPICAL PROPERTIES:

**SERVICE PRO® PREMIUM HD SINGLE-VISCOSITY
GRADE ENGINE OILS**

SAE Grade	10W	30	40
Gravity, ASTM D 4052, °API	30.0	28.3	27.7
Pounds Per Gallon	7.3	7.4	7.4
Flash Point, ASTM D 92 (COC), °F (°C)	439 (226)	(489 (254))	486 (252)
Viscosity, ASTM D 445, cSt at 100°C	6.6	12.0	14.9
ASTM D 445, cSt at 40°C	38.9	104	145
Viscosity Index, ASTM D 2270	126	105	103
HTHS Rate Vis at 150°C & 106 sec-1, cP	2.3	3.6	4.3
CCS Vis, ASTM D 5293, cP at °C	4520 at -25	NR*	NR*
MRV Vis, ASTM D 4684, cP at °C	17,800 at -30	NR*	NR*
MRV Yield Stress, ASTM D 4684, Pa at °C	<35 at -30	NR*	NR*
Pour Point, ASTM D 97, °F (°C)	-27 (-33)	-11 (-24)	+10 (-12)
Sulfated Ash, ASTM D 874, %m	1.0	0.9	0.9
TBN (Total Base No.), ASTM D	8.5	8	8
Color, ASTM D 1500 (may vary by location)	2.0	3.5	4.5
API Service Categories			
CF-2		X	X
CF	X	X	X
CD-II (obsolete)	X	X	X
CD (obsolete)	X	X	X
Approvals or performances that are Viscosity Grade specific:			
Allison C-4	X	X	
US CID A-A-52306		X	X

*NR = No Requirement