

SERVICE PRO[®]

Premium Lubricants

SERVICE PRO[®] PREMIUM MOTOR OILS

DESCRIPTION: SERVICE PRO[®] Premium Motor Oils are formulated to provide engine protection under severe operating conditions. SERVICE PRO[®] Premium Motor Oils are blended from selected and highly refined base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SERVICE PRO[®] Premium Motor Oils may be used over a wide temperature range. It also permits easier cold weather starting and helps minimize engine friction at start-up.

Recommended for automotive gasoline engines, including those equipped with superchargers, used in passenger cars, light trucks, power boats, motorcycles and other mobile and stationary equipment.

Meets API Service Category SN, SM, SL, SJ.

**PERFORMANCE
BENEFITS:**

- Resisted breakdown under high temperatures
- Maintained oil pressure under heavy load conditions
- Minimized rust and corrosion
- Good low temperature pour point

**TYPICAL
PROPERTIES:**

SAE Grade	10W40	20W50
Viscosity		
@40 Deg. C, cSt	100.5	165
@100 Deg. C, cSt	14.1	18
Viscosity Index	144	120
Sulfated Ash, %wt.	<1.0	<1.0
Pour Point Deg. F	-30	-27
Service Pro Part #	17134	17205



Updated: 02/11

SPWNPCMO

SERVICE PRO[®]

Premium Lubricants

SERVICE PRO[®] PREMIUM SINGLE GRADE MOTOR OILS

DESCRIPTION: SERVICE PRO[®] Premium Single Grade Motor Oils are formulated to provide engine protection under severe operating conditions. Made from selected and highly refined base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SERVICE PRO[®] Premium Single Grade Motor Oils are recommended for all major automotive gasoline and LPG powered engines for passenger cars, pickup trucks, vans and SUV's. Meets current API licensing Service Category SN, as well as former API Classifications SM, SL, SJ, SH. SERVICE PRO[®] Premium Single Grade Motor Oils are especially recommended for use in automotive applications involving high temperatures and type service such as hauling boats and camping trailers at sustained high speeds for long periods of time. In all cases, the car or engine manufacturer's lubricant recommendations for API performance category and SAE viscosity grade should be followed.

TYPICAL PROPERTIES:	SAE Grade	30	40
API Gravity		28.4	27.5
Pounds per gallon		7.37	7.42
Pour point, Deg. F		-20	-10
Viscosity			
40 Deg C, cSt		81.5	129.2
100 Deg C, cSt		10.02	13.7
Viscosity Index		107	102
Flash Point Deg. F		+450	+450
Sulfated Ash, % wt.		<1.0	<1.0
Service Pro Part #		17057	17057



Updated: 02/11
SPWN5GPCMO