

SERVICE PRO[®]

Premium Lubricants

SERVICE PRO[®] PREMIUM MOTOR OILS

DESCRIPTION: SERVICE PRO[®] Premium Motor Oils are formulated to provide engine protection under severe operating conditions. SERVICE PRO[®] Premium Motor Oils are blended from selected and highly refined base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SERVICE PRO[®] Premium Motor Oils may be used over a wide temperature range. It also permits easier cold weather starting and helps minimize engine friction at start-up.

Recommended for automotive gasoline engines, including those equipped with superchargers, used in passenger cars, light trucks, power boats, motorcycles and other mobile and stationary equipment.

Meets API Service Category SM, SL, SJ complies with ILSAC GF-3 requirements.

PERFORMANCE BENEFITS:

- Resisted breakdown under high temperatures
- Maintained oil pressure under heavy load conditions
- Minimized rust and corrosion
- Good low temperature pour point

TYPICAL PROPERTIES:

SAE Grade	10W40
Viscosity	
@40 Deg. C, cSt	100.5
@100 Deg. C, cSt	14.1
Viscosity Index	144
Sulfated Ash, %wt.	<1.0
Pour Point Deg. F	-30
Service Pro Part #	17134



SERVICE PRO[®]

Premium Lubricants

SERVICE PRO[®] PREMIUM SINGLE GRADE MOTOR OILS

DESCRIPTION: SERVICE PRO[®] Premium Single Grade Motor Oils are formulated to provide engine protection under severe operating conditions. Made from selected and highly refined base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SERVICE PRO[®] Premium Single Grade Motor Oils are recommended for all major automotive gasoline and LPG powered engines for passenger cars, pickup trucks, vans and SUV's. Meets current API licensing Service Category SM, as well as former API Classifications SL, SJ, SH. SERVICE PRO[®] Premium Single Grade Motor Oils are especially recommended for use in automotive applications involving high temperatures and type service such as hauling boats and camping trailers at sustained high speeds for long periods of time. In all cases, the car or engine manufacturer's lubricant recommendations for API performance category and SAE viscosity grade should be followed.

TYPICAL PROPERTIES:	SAE Grade	30
	API Gravity	28.4
	Pounds per gallon	7.37
	Pour point, Deg. F	-20
	Viscosity	
	40 Deg C, cSt	81.5
	100 Deg C, cSt	10.02
	Viscosity Index	107
	Flash Point Deg. F	+450
	Sulfated Ash, % wt.	<1.0
	Service Pro Part #	17057

