

SERVICE PRO®

Premium Lubricants

SERVICE PRO® PREMIUM MULTI VEHICLE SYNTHETIC BLEND ATF

DESCRIPTION: SERVICE PRO® Premium Multi Vehicle Synthetic Blend ATF is a new generation automatic transmission fluid recommended for use in automobile and truck transmissions, power-shift transmissions and other types of service requiring an approved Ford Mercon® V, Mercon®, Dexron® III-H or Allison C-4 automatic transmission fluid. It is approved for use in Voith Transmissions. Approved for ZF applications TE-ML 03D, 04D, 14B, 16L and 17C.

SERVICE PRO® Premium Multi Vehicle Synthetic Blend ATF is also recommended for service fill in Mercon, Chrysler, Honda/Acura, Hyundai, Jeep, Mercedes-Benz, Mitsubishi (Diamond SP-II or SP- III), Nissan (Matic D, J or K)/Infiniti, Saturn, Toyota (T-III & T-IV)/Lexus/Scion, VW/Audi, most European vehicles including BMW & Volvo, most Asian vehicles including Daewoo, Isuzu, Kia, Mazda, and Suzuki.

SERVICE PRO® Premium Multi Vehicle Synthetic Blend ATF is not for use in transmissions requiring Ford Type F or Dexron® VI, Mercon® SP, LV or in Continuously Variable Transmission (CVT) applications. Always consult your owner's manual where specific automatic transmission fluids are recommended.

PERFORMANCE BENEFITS:

- Outstanding resistance to oxidative and thermal breakdown
- Exceptional low temperature fluidity
- Excellent anti-wear properties.
- Stable friction properties
- Excellent gear shift quality throughout service life.

TYPICAL PROPERTIES:

Gravity, API	33.2
Density, lbs/gals	7.14
Flash, COC, °F	352
Viscosity	
@ 40 Deg. C, cSt	34.9
@ 100 Deg. C, cSt	7.93
Viscosity Index	210
Brookfield Viscosity cP @ -40°C	
Max	12,000
Color	Red
Voith	Service bulletin #013 & 118
ZF	TE-ML 03D, 04D, 14B 16L, 17C





SERVICE PRO[®]

Premium Lubricants

SERVICE PRO[®] PREMIUM MULTI VEHICLE SYNTHETIC BLEND ATF

Service Pro Multi-Vehicle Synthetic Blend ATF is suitable for use in the following applications:

Allison C-4	Mercedes-Benz 236.3
Audi G-052-025-A2	Mercedes-Benz 236.5
Audi G-052-025-A1	Mercedes-Benz 236.7
BMW LA2634	Mercedes-Benz 236.9
BMW LT71141	Mercedes-Benz 236.10
Dexron [®]	Mitsubishi Diamond SP-II
Dexron [®] -II	Mitsubishi Diamond SP-III
Dexron [®] -III D	Nissan Matic-D
Dexron [®] -III G	Nissan Matic-J
Dexron [®] -III H	Nissan Matic-K
Esso LT 71141	Shell LA2634
Ford Mercon [®]	Subaru ATF HP
Ford Mercon [®] V	Texaco 7045-E
Honda/Acura ATF-Z1 (except CVT's)	Texaco ETL-8072 B
Hyundai SP-II	Texaco N402
Hyundai SP-III	Toyota Type T-III
Idemitsu K17	Toyota Type T-IV
JWS 3309	Voith 55.6335.32 (G607)
Kia SP-II	Volvo 97340
Kia SP-III	ZF TE-ML 03D
MAN 339 V1	ZF TE-ML 04D
MAN 339 Z1	ZF TE-ML 14A
MAN 339 Z2	ZF TE-ML 14B
Mazda ATF-111	ZF TE-ML 16L
Mazda ATF-MV	ZF TE-ML 17C